


Double Slider

- Operating unit with both sash opening and closing from side to side.
- Sash glide smoothly on corrosion-resistant brass rollers.
- Meeting stile has an interlocking design to secure sash tightly together around weatherstripping.
- Sash lift out to allow cleaning of the exterior glass from the inside.



Standard Features

Frame Type	Replacement (no nailing fin)
Exterior Frame Design	Contoured
Frame Construction	Welded
Sash Construction	Welded
Jamb Thickness	3-1/4"
Vinyl Profile	Chambered
Vinyl Color	White
Spacer System	Intercept®
Insulating Glass Unit	3/4"
Glass	Low E / Argon-filled
Glass Type	Clear
Glass Strength	Single
Weatherseals	Finseal and Sill Bulb Barrier
Meeting Stile	Interlocking Meeting Stile
Sash Operation	Brass Rollers
Cam Lock	Single: Units <24" Tip-to-Tip; Double: Units ≥ 24" Tip-to-Tip
Screen	Half, Fiberglass Extruded
Lift Rail	Extruded

Optional Features

Vinyl Color	Tan or Clay
Screen	Full, Fiberglass Extruded
Glass	Tempered, Tinted Bronze, Tinted Grey, Obscure
Colonial Grids	White, Tan, Clay or Brass
Prairie Grids	White, Tan, Clay or Brass
Perimeter Grids	White, Tan, Clay or Brass
Jamb Extensions	Quick Trim (clear), Wood (primed or stainable)